



All the dimensions are in mm .

Ref.	Dimensions
Flange	F03
C x depth	M5x8
E	36
B	9
O	10.2
A	134.6
G	10
H	20.2
I	9
J	24
K	18
L	80.4
M	32.7
N	47.7
P	34
Q	39
R	10.9
S	20
T	60.4
X	73
W	5

Double Acting Actuators - Output Torque related to rotation angle , in Nm
(0°valve closed 90°valve open)

ROTATION ANGLE	Air pressure supply in bar							
	2,5	3	4	5	5,6	6	7	8
0°	13.4	16.1	21.4	26.8	30.0	32.1	37.5	42.9
50°	6.7	8.0	10.7	13.4	15.0	16.1	18.8	21.4
90°	10.0	12.1	16.1	20.1	22.5	24.1	28.1	32.1

Technical Data

Max Pressure	** Min Pressure	Rotation	Stroke Adjustment	Screw Stroke Adjustment	*Moving time (sec.)		Operating temperature (°C)
					Opening	Closing	
8.4 bar	1 bar	92° -1° +91°	-	-	0.06	0.07	Standard -20°C +80°C High temperature -20°C +150°C Low temperature -50°C +60°C

Weight Kg	Chamber Ø (mm)	Air volume L/cycle
1.3	40	0.148

****Attention: for "High Temperature" and "Low Temperature" version, the Min Pressure is 3 bar.**

*The moving time could vary on different operating and installation factors .