



All the dimensions are in mm .

Ref.	Dimensions
Flange	F16
D x depth	M20X30
F	165
B	46
O	50.5
A	1001
G	18.5
I	32
L	314.5
M	148.5
N	166
P	120.4
Q	120.4
R	46
S	30
T	240.8
W	3/8" GAS
Z	857
Ch	24

**Spring return Actuators Normally Closed (N.C.) - Output Torque related to rotation angle , in Nm
(0°valve closed 90° valve open)**

Spring Torque	Air pressure supply in bar																																
	2,4			2,8			3			3,5			4,2			5			5,6			6			7			8					
SIZE	0°	50°	90°	0°	50°	90°	0°	50°	90°	0°	50°	90°	0°	50°	90°	0°	50°	90°	0°	50°	90°	0°	50°	90°	0°	50°	90°	0°	50°	90°			
2,8	640	480	960	731	343	411	960	480	640	1074	549	754	1360	720	1040	1760	960	1440															
3,5	800	600	1200							914	429	514	1200	600	800	1600	840	1200	2057	1114	1657	2400	1320	2000									
4,2	960	720	1440										1040	480	560	1440	720	960	1897	994	1417	2240	1200	1760	2469	1337	1989	3040	1680	2560	3611	2023	3131
5,6	1280	960	1920																1577	754	937	1920	960	1280	2149	1097	1509	2720	1440	2080	3291	1783	2651

Technical Data

Max Pressure	** Min Pressure	Rotation	Stroke Adjustment	Screw Stroke Adjustment	*Moving time (sec.)		Operating temperature (°C)
					Opening	Closing	
8.4 bar	2.4 bar	92° -1° +91°	10 °	-	7	8	Standard -20°C +80°C Low temperature -50°C +60°C

Weight Kg	Chamber Ø (mm)	Air volume L/cycle
67	208	12.5

****Attention: "Low Temperature" version is not available with 2.8 Spring Torque Size and the Min Pressure is 3.5 bar.**

*The moving time depend on different operating end installation factors .